

VDP-K203 Four-Wire Analog Bundle




- Water Proof Analog Kit for villa or house, only one call button
- Kit including DS-KB2421T-IM and DS-KH2220, 5-meter 4-wire cable, and other accessories
- European power supply adaptor included (please mark for other standards when you order)

▪ Specification

Door Station	
Resolution	1920 × 1080 Stream resolution: 960 × 576
Lens	1/2.7" CMOS
FOV	Horizontal: 66.2° Vertical: 37.2°
Door Station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Door station	
I/O output	1 relay output
Four-wire	1-ch video input, 1-ch audio input/output, 1-ch power supply, 1-ch grounding
Door station	
Power supply	12 VDC
Power consumption	Max. 5 W
Working temperature	-10° C to + 55° C (14° F to 131° F)
Working humidity	10% to 90%
Dimensions	128 mm × 42 mm × 24.8 mm
Protective level	IP65
Indoor station	
Operation method	Physical button
Type	7-inch colorful TFT LCD
Resolution	800 × 480
Indoor station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Indoor station	
Power supply	12 VDC
Power consumption	≤ 5 W
Working temperature	-10° C to + 55° C (14° F to 131° F)
Working humidity	10% to 90%
Dimensions (W × H × D)	195.8 mm × 132.8 mm × 18.39 mm (7.7" × 5.2" × 0.7")

▪ Dimension



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq