



DTE-110-AI

Fixed + rate of rise heat detector with isolator 58°C

Description

The DTE-110-AI fixed + rate of rise heat detector with isolator has been designed based on the latest technological advances on the market. Its European design makes the 100 range an ideal option for those installations where the balance between functionality and aesthetics is necessary. It uses a communication protocol with great stability based on the Ultrafast frequency analysis, thanks to its Ed-Fast Search technology performs one of the fastest readings on the market, providing all the information in a short space of time.

The 100 series fixed + rate of rise heat detectors are based on the control of the temperature increase by means of low thermal mass thermistor. Temperature 58 °C.

Addressing of this range can be done:

- Using PGE-100 manual programming tool.
- By serial number of the devices
- By app via Bluetooth
- Through auto-addressing

Applications

Thanks to the control of its intelligent sensor, the range of fixed + rate of rise detectors of the EASY DETECT 100 series is defined as a reliable fire detection system for those fire occurrences that start with a sudden rise in the temperature. This type of detector is suitable where smoke detectors are less effective and require greater temperature sensitivity (Kitchen / Ventilation areas / Boiler rooms / Laundries / Workshops).

Features

- Made in Spain
- Intelligent decision algorithm
- Parallel indicator output
- Ultrafast Protocole

Technical Features

DETECTOR	Loop Features:	
	Working voltage:	From 22 to 38VDC
	Consumption in rest:	< 100 µA
	Consumption in alarm:	< 100 mA
CONNECTION	2 x 1,5 mm ² braided and shielded connection to ZCE-100 base	
ENVIRONMENT	Working temperature:	From -10 °C to 70°C
	Relative humidity:	95% without condensation
	IP Index:	IP20
PHYSICAL	Head (height x diameter):	60 mm x 104 mm
FEATURES	Material:	ABS
CERTIFICATION	EN 54-5 DTE-110-AI	

