



MAE-541-I

Addressable 1-zone monitor module for conventional equipment with isolator

Description

Addressable 1-zone monitor module for conventional equipment with built-in isolator to control the connection of up to 32 conventional detectors and / or 10 conventional call points per zone. With AF Ultrafast communication protocol. It discriminates between call point and detector together with fault or short circuit in the zone. Requires 24Vdc auxiliary power supply occupying one address in the loop per zone. Small box with LED status indicator with 180° display. Individual removable strips. Allow non-polar installation on DIN or flat rail with the possibility of incorporating a ONE-BOX or SIX-BOX box. Black and white color. Dimensions 92 x 105 x 22 mm.

Addressing of this range can be done:

- Using PGE-100 manual programming tool
- By serial number of the devices.
- By app via Bluetooth
- Through self-programming

Applications

They are ideal for saving money when connecting a number of conventional detectors or call points in the same area, that have the same address. Parking lots, open spaces, etc.

Features

- Made in Spain
- LED status indicator 180°
- Removable terminal block
- Protection box
- CPR EN54-18 / EN54-17 certified
- Rail din

Technical Features

MODULE	Loop Features	Working voltage:	From 31 to 40VDC
		Consumption in rest:	< 300 µA
		Consumption in alarm:	< 3mA
		Relay Contact:	1 A @ 30VDC
	Auxiliary power supply:	Working tension	24VDC
		Consumption in rest:	< 5 mA x Zone
		Consumption in alarm:	< 100 mA x Zone
CONNECTION		2 x 1.5 mm ² braided and shielded	
ENVIRONMENT	Working temperature:	From -10°C to 40°C	
	Relative humidity:	95% non-condensin	
	IP Index:	IP40	
PHYSICAL FEATURES	Size	92 mm x 105 x 22 mm	
	Material:	ABS	
CERTIFICATION		EN 54-18 / EN54-17	